

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)


PCT

(10) International Publication Number
WO 2005/060090 A1

- (51) International Patent Classification⁷: **H03G 3/00**,
H03F 1/02, 3/45
- (21) International Application Number:
PCT/EP2004/014169
- (22) International Filing Date:
13 December 2004 (13.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
03293116.4 12 December 2003 (12.12.2003) EP
- (71) Applicant (for all designated States except US):
FREESCALE SEMICONDUCTOR, INC. [US/US];
6501 William Cannon Dr., Austin, TX 78735 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **TRAUTH, Gerhard**
[FR/FR]; 85, avenue Baiovilla, F-31600 Muret (FR).
ODDOART, Ludovic [FR/FR]; 7, rue Painleve, F-31270
Frouzins (FR). **TRICHET, Jacques** [FR/FR]; 10, impasse
de la Cassagnere, F-31270 Cugnaux (FR). **VANHUFFEL,**
Vincent [FR/FR]; 11, rue Gilbert Affre, F-31830 Plaisance
du Touch (FR).
- (74) Agent: **WHARMBY, Martin, A.**; c/o Impetus IP Ltd,
Grove House, Lutyens Close, Chineham Court, Bas-
ingstoke, Hampshire RG24 8AG (GB).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.
- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: A POWER AMPLIFIER MODULE AND A TIME DIVISION MULTIPLE ACCESS RADIO



(57) Abstract: A power amplifier module (200) comprises a power amplifier circuit (201) having an output power level controlled by a power supply voltage. A power supply transistor (207) controls the power supply to the power amplifier circuit (201) from a drive signal which is received from a drive circuit (209). The drive circuit (209) generates the drive signal in response to a power level input signal, which specifically may correspond to a power ramping for a GSM cellular communication system. The power amplifier module (200) furthermore comprises a detection circuit (211) which determines an operating characteristic of the power supply transistor (207). The operating characteristic is preferably a saturation characteristic. A control circuit (213) controls the drive signal in response to the operating characteristic. The control circuit (213) preferably controls the drive signal such that the power supply transistor (207) does not enter the linear region for a Field Effect Transistor and the saturated region for a bipolar transistor.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.